



## **HAIL DAMAGE Permit Submittal Guide**

### **Siding Replacement & Roof Re-Covering or Re-Shingling Permit Submittal and Installation Guide**

All work must conform to the 2015 International Residential Code including Chapters 7, 8 and 9.

**Please utilize the checklist below before submitting an application:**

#### **Roof Replacement or Recovering**

- 1 - R803 / T 803.1 - Lumber sheathing.
- 2 - R803.2.2 - Allowable spans for roof sheathing.
- 2a - R503.2.1.1[1] - Allowable spans for Structural Panel [ Plywood ] Roof Sheathing.
- 3 - R302 Fire Resistant Construction
- 3a - R302.2.1 - Townhouse Continuity - Fire rating sheathing is required within 4 feet of a wall at adjoining occupancies.
- 3b - R302.2.2 – Parapets & exceptions for fire rated construction.
- 4 - R806.1.2 - Roof ventilation of 1/150<sup>th</sup> of the area with exceptions listed.
- 5 - R807.1 – Required attic access and openings.
- 6 - R903 / R903.2 – Weather Protection / Flashing – Eaves, Walls.
- 7 – R905.1.1 - Underlayment
- 8 - Roof Coverings
- 8a - R905.1.1 – Underlayment.
- 8b - R905.1.2 - Ice and Water Shield.
- 8c - Table R905.2.4.1 - Classification of Asphalt Roof Shingles.
- 8d - R905.2.5 / 905.2.6 – Shingle Fasteners.
- 8e – R905.2.8.5 – Drip Edge R905.3.8 – Flashing.
- 8f – R905.3.8 – Flashing Other.
- A Building Permit and Inspections are required.

## **EXTERIOR WALL RECOVERING / RE-SIDING**

- 1 – R703.1 / RR703.1.1 – Water Resistive barrier required under veneer.
- 2 – Siding attachment and minimum thickness
- 3 - Flashing
- 4 – A building permit is NOT required, however, these code sections still apply.

**Building Inspection for Roof Re-Covering ONLY consists of a Final Inspection after completion of the project.**

**Additional Permits and inspections are required for specific items listed above when additional items are known at permit application or are discovered at roof re-covering inspection.**